

Pressure- Temp
Chart

| Temp °F | OZ-12 psig |
|---------|------------|
| -40 | -6 |
| -35 | -3 |
| -30 | 0.2 |
| -25 | 1.9 |
| -20 | 3.9 |
| -15 | 6 |
| -10 | 8.3 |
| -5 | 10.7 |
| 0 | 13.4 |
| 5 | 16.3 |
| 10 | 19.4 |
| 15 | 22.7 |
| 20 | 26.3 |
| 25 | 30.2 |
| 30 | 34.3 |
| 35 | 38.6 |
| 40 | 43.3 |
| 45 | 48.3 |
| 50 | 53.5 |
| 55 | 59.1 |
| 60 | 65 |
| 65 | 71.3 |
| 70 | 77.9 |
| 75 | 84.9 |
| 80 | 92.3 |
| 85 | 100 |
| 90 | 108.2 |
| 95 | 116.8 |
| 100 | 125.8 |
| 105 | 135.3 |
| 110 | 145.2 |
| 115 | 155.5 |
| 120 | 166.4 |
| 125 | 177.7 |
| 130 | 189.6 |
| 135 | 201.9 |
| 140 | 214.8 |
| 145 | 228.2 |
| 150 | 242.2 |

Trade Name(s) OZ-12 - OZ Technology
Formula R-290/600 (60/40)
Chemical Name
Lube ALL
Replaces R12

OZ-12

This information is believed to be accurate and reliable but is provided for guidance only. A-Gas accepts no responsibility and the user assumes all risks and liability for use of this information.